

The Integrated ID Card Printer + Laminator

The high-security Magicard Tango +L integrated ID card printer and laminator features a robust metal construction for quality printing and lamination, and long-term reliability. With a Plug and Play Windows driver, standard Ethernet and USB for flexible interfacing, and both hardware and software printer locking facilities, the Tango +L is the professional's choice.



The Tango +L laminates cards for increased visual security, and to protect cards against physical damage for a longer lifetime. Lamination extends card life to 10,000's of swipes, suitable for high-use applications like access control, and many years of use in driver's license or other government card applications.

- SECURE** Standard & Custom holographic laminates and Custom HoloKote® watermark
- FLEXIBLE** Ethernet, USB, Parallel all fitted as standard
- SMART** New Plug and Play driver for ease of use
- TOUGH** Robust metal construction



Tango +L is supplied with a free, three year warranty with hassle-free printhead cover and loaner service.
(Available in the North America, EU and selected other countries only)





Integrated ID Card Printer + Laminator

Specify your Tango +L

Specifications

Operation	Single and double-sided printing and lamination. Integrated card flipper turns cards over to enable double-sided printing and lamination.
Card Security	Standard and Custom Holographic Laminate films. The user has the option to print a HoloKote® transparent security watermark across the card surface. The HoloKote watermark can be customized when a Custom Key is ordered.
Printer Security	Locking card hopper, card stacker, card reject tray and lamination film spools.
Warranty	In North America, EU and other selected countries, the Tango +L comes with three years FREE UltraCoverPlus warranty which includes full printhead cover and free loaner service. Elsewhere 12 months limited warranty.
Printer Interfaces	USB, Parallel, and Ethernet interfaces included as standard.
Software Drivers	Windows 2000, 2003 Server user-mode, XP drivers all supplied with printer.
Card Capacity	100 cards feed hopper, 50 cards output stacker.
Weight	44lbs (20 kg)
Dimensions	29" long x 12" wide x 10" high including hopper & stacker. 740mm long x 300mm wide x 260mm high.
Environment	Sheltered Office environment 50°F to 85°F (10°C to 30°C).
Print Speed	Print & laminate card (single-sided) : between 36 & 55 seconds depending on settings. Print & laminate card (double-sided) : between 82 & 120 seconds depending on settings.

Custom Laminates

Full custom laminates, for the highest security.



HoloKote Custom Key

Custom Key for custom HoloKote cards and for locking the printer.



Consumables

Dye Film	LC1 : YMCKO 5 panel dye film 350 images per roll (Part No. M9005-751). LC3 : Monochrome resin black 1000 images per roll (Part No. M9005-753). Range of color ribbons (red, blue, green, gold, silver or white) 1000 images per roll. LC6 : KO 2 panel dye film (black and overcoat) 600 images per roll (Part No. M9005-756). LC8 : YMCKOK 6 panel dye film 300 images - (Part No. M9005-758).
Lamination Film	Clear and holographic laminates available in both Patch and Thin film formats. Custom holographic laminates available. Patch laminates available in 0.6 mil and 1.0 mil thicknesses.
Card Types	PVC/Polyester composite ISO CR80 sized cards.
Card Thickness	0.03" (0.76mm).

Magnetic Stripe

HiCo/LoCo magstripe encoder for time and attendance and access control.



Options

Anti-Counterfeiting	Custom Key . Prints customer specific HoloKote watermark into the card overcoat across the entire card face.
Magstripe Encoder	HiCo/LoCo Magstripe encoder ISO Std. 7811 and customer formats - can be combined with chip encoder.
Smart Card Encoder	Chip Contact programming facility for smart cards.
Contactless Card Encoder Options	Mifare, HID i-Class, Inside Technologies, Desfire options available.

Chip Encoding


Chip and contactless (proximity) card encoding in the printer for multi-function security cards.



MagiCard, HoloPatch and HoloKote are trademarks of Ultra Electronics Limited. Windows 2000 and XP are trademarks of Microsoft Corporation. The information contained in this document reflects the current state of design and we reserve the right to change the specification without notice or obligation.

Variants

M9007-125E	MagiCard Tango +L Integrated ID Card Printer & Laminator 115V.
M9007-208E	MagiCard Tango +L Integrated ID Card Printer & Laminator 240V.
M9007-214E	MagiCard Tango +L Integrated ID Card Printer & Laminator with built-in Magstripe Encoder 115V.
M9007-215E	MagiCard Tango +L Integrated ID Card Printer & Laminator with built-in Magstripe Encoder 240V.



2ppUSLTR/T+L/0407/ENG



Ultra Electronics Card Systems

North American Sales & Support Center
6711 - 176th Avenue, NE Redmond WA 98052
Toll Free: 877 236 0933 **Tel:** (425) 556 9708
Fax: (425) 556 3962
email: USsales@UltraMagicard.com



Ultra Electronics Card Systems

Hampshire Road, Weymouth,
Dorset DT4 9XD, United Kingdom
Tel: +44 (0) 1305 784 738
Fax: +44 (0) 1305 777 904
email: UKsales@UltraMagicard.com



MAGICARD

Secure ID card printers

www.magicard.com